



Made of special carbide with extreme high hardness and toughness. The tool come with a layer of extreme coating. It has extreme high hardness and excellent thermal and chemical stability can protect the tool against permature wear. Stub length offer rigidity when it engage in cutting. These tools also offer strength to combat deflection due to overhang. These ball end mill for milling fillets or similar rounded corners in the bottom of cut on Hardened Steel up to HRC65.. Stub length offer rigidity and reduce deflection when it engage in cutting.

EDP #	MILL Ø	LOC	SHK Ø	OAL
E841426020	2.0	4.0	4.0	38.0
E841426025	2.5	5.0	4.0	38.0
E841426030	3.0	5.0	4.0	38.0
E841426035	3.5	6.0	4.0	38.0
E841426040	4.0	7.0	4.0	38.0
E841426045	4.5	8.0	5.0	38.0
E841426050	5.0	8.0	5.0	38.0
E841426055	5.5	8.0	6.0	38.0
E841426060	6.0	8.0	6.0	38.0
E841426065	6.5	10.0	8.0	42.0
E841426070	7.0	10.0	8.0	42.0
E841426075	7.5	11.0	8.0	42.0
E841426080	8.0	11.0	8.0	42.0
E841426085	8.5	11.0	10.0	48.0
E841426090	9.0	11.0	10.0	48.0
E841426095	9.5	13.0	10.0	48.0
E841426100	10.0	13.0	10.0	50.0
E841426105	10.5	14.0	12.0	50.0
E841426110	11.0	14.0	12.0	50.0
E841426115	11.5	15.0	12.0	50.0
E841426120	12.0	15.0	12.0	55.0
E841426130	13.0	15.0	14.0	55.0
E841426140	14.0	15.0	14.0	58.0
E841426150	15.0	16.0	16.0	58.0
E841426160	16.0	18.0	16.0	62.0
E841426170	17.0	19.0	18.0	62.0
E841426180	18.0	20.0	18.0	70.0
E841426190	19.0	21.0	20.0	70.0
E841426200	20.0	22.0	20.0	75.0
E841426210	21.0	23.0	22.0	75.0
E841426220	22.0	24.0	22.0	75.0
E841426230	23.0	25.0	25.0	75.0
E841426240	24.0	26.0	25.0	75.0
E841426250	25.0	27.0	25.0	75.0

Malaysia Tel:+60-7-358-4585 Fax:+60-7-358-4586

Singapore Tel:+65-6742-6455 Fax:+65-67493776

Thailand Tel:+66-2-898-6653 Fax:+66-2-898-5356

**TNP**